

Meridian Gyrocompasses

Marine Navigation Systems

Highly accurate performance with low cost of ownership

The Meridian gyrocompass product range is suitable for the ever-changing needs of a modern integrated navigation bridge system. This includes highly accurate performance with low cost of ownership and system flexibility. Due to the Meridian's small size and fast settle time of less than 45 minutes, there are no limits to the type of vessel for which it is suitable.

The Meridian gyrocompass can be installed as a stand-alone unit or, together with any of the Meridian range of repeaters and ancillaries, it becomes a single, dual or triple gyro system. The Meridian can also be used to replace many existing gyrocompasses as a retrofit unit.

For simple installation the Meridian offers a large array of digital and analogue outputs plus easy to use set-up and self-test modes that are activated via the control unit. The versatility and flexibility of the Meridian can be clearly



demonstrated with the remote control unit option which gives freedom to install the main unit in the most convenient location whilst installing the remote control unit where it can be seen and regularly used.

Unlike other marine navigation gyrocompass currently available, the Meridian has a maintenance-free dry element with a meantime between failure of more than 30,000 hours; and post- installation there are no scheduled annual maintenance and servicing costs.

PRODUCT FEATURES

- Type approved to marine equipment directive
- Economic one-box solution
- Fast initial settle time
- Small, lightweight and versatile
- High dynamic heading accuracy
- Versatile range of repeaters and ancillaries
- Subsea variants also available



Meridian Standard

The heart of the Meridian gyrocompass is the element, which is a dynamically tuned gyroscope (DTG). The DTG is a high precision technology which, due to its size, accuracy, reliability and shock resistance, is used in many different applications.

The guaranteed accuracy of the Meridian gyrocompass is obtained through specialised high quality engineering. This gives exceedingly stable heading and means that the gyro will follow a high turn rate of up to 200° per second.




Meridian Surveyor

The Meridian Surveyor boasts a wide range of interfaces to enable use on any marine vessel. The unit utilises a DTG gyro element which provides exceptional performance with an accuracy unmatched by even the latest fibre optic designs.



Note: Subsea variants also available - see separate data sheet.

Remote Control Unit Option



For simple installation the Meridian offers a large array of digital and analogue outputs plus easy to use digital set-up and self-test modes that are activated via the control unit.

The versatility and flexibility of the Meridian gyrocompass can be clearly demonstrated with the remote control unit option, which is supplied with the gyrocompass system. This gives freedom to install the main unit in the most convenient location whilst installing the remote control unit where it can be seen and regularly used.

Meridian Gyrocompasses

Bearing Repeater

Data Repeater

PRODUCT FEATURES

- Precision 360° rotating compass card
- Automatic synchronisation with master compass
- Gimbal mounted
- Integrated illumination control
- Accepts true and magnetic heading data
- Suitable for use with either prism or vane type azimuth sights
- Pedestal stand and bulkhead bracket mounting options available



Power Supply Input	18 - 36Vdc (15W)
Signal Inputs	1 x IEC 61162 (NMEA 0183) 1 x step (5-70Vdc)
Signal Outputs	1 x IEC 61162 (NMEA 0183)
Environmental and EMC	Meets or exceeds IEC 60945 weather exposed equipment
Physical	Dimensions: 287mm x 388mm x 388mm

PRODUCT FEATURES

- Clear vacuum fluorescent graphics display
- User selection of display format - simulated 360° tape/ digital heading/digital ROT
- Suitable for steering repeater
- Integral illumination control
- Accepts true and magnetic heading sentences Second input for magnetic correction
- Supplied with swivel bracket for bulkhead or table mounting
- DIN front panel for console mounting



Power Supply Input	18 - 36Vdc (6W)
Signal Inputs	1 x IEC 61162 (NMEA 0183) 1 x step (5-70Vdc)
Signal Outputs	1 x IEC 61162 (NMEA 0183)
Environmental and EMC	Meets or exceeds IEC 60945 weather protected equipment
Physical	Dimensions: 96mm x 192mm x 145mm



Azimuth Circle
(Prism and Vane Types)



Pedestal Stand



Bulkhead Bracket

Digital Repeater

PRODUCT FEATURES

- 4-digit LED heading display
- LED turning indicator
- Integral illumination control
- Accepts true and magnetic heading sentences
Second input for magnetic correction
- Supplied with swivel bracket for bulkhead or table mounting
- DIN front panel for console mounting



Power Supply Input	18 - 36Vdc (10W)
Signal Inputs	1 x IEC 61162 (NMEA 0183) Heading 1 x IEC 61162 (NMEA 0183) Magnetic correction 1 x step (5-70Vdc)
Signal Outputs	1 x IEC 61162 (NMEA 0183)
Environmental and EMC	Meets or exceeds IEC 60945 weather protected equipment
Physical	Dimensions: 96mm x 192mm x 145mm

Dial Repeater

PRODUCT FEATURES

- Precision 360° rotating compass card
- Automatic synchronisation with master compass
- Integrated illumination control
- Supplied with swivel bracket for bulkhead or table mounting
- DIN front panel for console mounting



Power Supply Input	18-31.6 Vdc (6W)
Signal Inputs	1 x IEC 61162-1 (NMEA 0183), Baud rate 4800, 9600, 19200, 38400
Environmental and EMC	Meets or exceeds IEC 60945 weather protected equipment
Physical	Dimensions: 144mm x 144mm x 100mm including connector Weight: 1.25 Kg Connector: 15-way subminiature plug (2.5m cable supplied) Dial marking: 1°, 5°, 10°, 45°

Heading Repeater

PRODUCT FEATURES

- Large, clear vacuum fluorescent graphics display
- User selection of display format - simulated 360° tape/digital heading/digital ROT
- Dual input - compass comparator display
- Suitable for steering repeater
- Integral illumination control
- Supplied with swivel bracket for bulkhead or table mounting
- DIN front panel for console mounting



Power Supply Input	18 - 36Vdc (15W)
Signal Inputs	2 x IEC 61162 (NMEA 0183) 1 x Step (5-70Vdc) 1 x Synchro (option)
Signal Outputs	1 x IEC 61162 (NMEA 0183)
Environmental and EMC	Meets or exceeds IEC 60945 weather protected equipment
Physical	Dimensions: 144mm x 288mm x 130mm

Step Retransmission Unit

PRODUCT FEATURES

- Converts 5V step code from gyrocompass to 24V, 35V, 50V or 70V power output
- Isolated input
- 4 output channels each independently protected against overloads
- Unit operates from 24Vdc – step supply internally generated



Power Supply Input	18 - 36Vdc (100W)
Signal Inputs	1 x step (5Vdc) 6 steps per degree
Signal Outputs	4 x step (24V, 35V, 50V or 70V) 1 x step (5Vdc) 1 x alarm relay (voltage free contacts)
Environmental and EMC	Meets or exceeds IEC 60945 weather protected equipment
Physical	Dimensions: 400mm x 300mm x 120mm

Note: A Compass Comparator System is also available to meet DNV requirements for dynamic positioning operations - see separate data sheet.

Meridian Gyrocompasses

Marine Navigation Systems

TECHNICAL SPECIFICATIONS

		Standard	Surveyor
Display		360° compass card and digital display	
Performance	Settle point error	0.25° secant latitude	0.10° secant latitude
	Settle point repeatability	0.25° secant latitude	0.10° secant latitude
	Static accuracy	0.10° RMS secant latitude	0.05° RMS secant latitude
	Dynamic accuracy	0.30° secant latitude	0.20° secant latitude
		scorsby/intercardinal motion	scorsby/intercardinal motion
	Follow-up speed	~200°/second	
	Settling time	<45 minutes to within 0.70° (from initial 30°)	
Outputs	S' type	1 x Step by Step (5V TTL), 6 steps per degree	
	Synchro	1 x 26V 400Hz sector value 360° (1:1 ratio) 11.8V line to line	
	Serial data	11 x RS422, NMEA 0183 (IEC 61162-1/2)	5 x RS422, NMEA 0183 (IEC 61162-1/2)
		5 x RS232, NMEA 0183	
		1 x printer port, NMEA 0183	5 x 20mA current loop
		1 x ROT (±10V)	
	Status/alarm	5V TTL power fail/gyro fail	
		5V TTL system ready	
		Potential free status and alarm relays	
Inputs	Latitude	Automatic - via RS232 or RS422, NMEA 0183 from GPS or manual	
	Speed	Automatic - via RS232 or RS422, NMEA 0183 from log or pulse/contact closure at 100, 200 or 400/NM from log or manual	
Compensation	Latitude	80°N to 80°S	
	Speed	0-90 knots	
Environmental	Ambient operating temperature	0°C – 45°C (–15°C – +55°C with reduced accuracy)	
	Storage temperature	–25°C – +80°C	
	Gimbal limits	±45° roll and pitch	
	Mean time between failures (MTBF)	>30,000 hours (calculated); >100,000 hours (in service data)	
	Shock (survival)	10g	
Operating Voltage	Input voltage	24Vdc (19-36Vdc)	
Power	Start-up	>3A at switch on / <1.5A in ready mode	
Dimensions	Size	344mm (h) x 267mm (w) x 440mm (d)	
	Weight	15.5 Kg	
Accessories	Included	Operator handbook, spare fuse	Operator manual, transit case, spare connector
	Optional	Remote control unit, various repeaters and accessories	
Standards		IMO A424(X1), IMO A821(19), IEC 60945, ISO 8728, ISO 16328, IEC 62288, Marine Equipment Directive 96/98/EC	
Warranty	24 months international warranty including parts and labour.		

COMPANY WITH
MANAGEMENT SYSTEMS
CERTIFIED BY DNV
= ISO 9001 =
= ISO 14001 =

Specifications subject to change without notice.
© 2014 Teledyne TSS, Inc. All rights reserved.



www.teledyne-tss.com
Email: tss_salesenquiries@teledyne.com

Head Office
1 Blackmoor Lane,
Croxley Green Business Park,
Watford, Hertfordshire
WD18 8GA, UK
Tel: +44 (0)1923 216020
Fax: +44 (0)1923 216061

Aberdeen
10 The Technology Centre,
Aberdeen Science & Energy Park,
Claymore Drive, Bridge of Don,
Aberdeen AB23 8GD, UK
Tel: +44 (0)1224 707081
Fax: +44 (0)1224 707085

Houston
7701 West Little York, Suite 300,
Houston, TX 77040, USA
Tel: +1 713 461 3030
Fax: +1 713 461 3099